

OPEN SURVEILLANCE STORAGE SYSTEM  
**COLDSTORE OPUS<sup>®</sup>**  
4U



COLDSTORE Opus 4U is used in very large systems with high camera counts



## An open VMS storage system with petabyte capacity and very low TCO

COLDSTORE's mirrored recording and sequential writing pattern across the array offers extreme hard disk reliability and very low power consumption.

- | Network attached sequential storage system designed for video
- | Incorporates LAID™ for low power and high disk reliability
- | Massive 1248TB maximum capacity using 26TB drives
- | Immediate compatibility with future larger disks
- | Only 175 watts power consumption fully populated
- | Uses any make/model of standard SATA drive
- | Supports all Video Management System brands
- | Reliable and proven COLDSTORE technology





# The COLDSTORE Opus series works with any Video Management System which supports external storage

COLDSTORE Opus 4U is ideal for projects requiring extremely high storage capacity, extended disk lifetimes, long file-retention and very low power consumption.

## Reliability Assured

Our Linear Array of Idle Disks (LAID™) technology produces a powerfully simple and reliable system which provides generous video storage capacity at low cost. Whilst simple in concept, it has far-reaching beneficial effects and delivers a highly reliable storage system which dramatically extends disk lifetime, even when using the lowest-cost disks available.

## Low Power, Low Cost

COLDSTORE Opus 4U is designed for larger installations, with longer retention times, providing extreme capacity in a 4U format, with power consumption as low as 0.2W per TB. It's aimed at projects with typical camera counts of up to 256 channels with high bit-rates. 1 gigabit and 2.5 gigabit Ethernet ports handle all video traffic from the VMS or NVR system.

## Extended Disk Lifetimes

Disks are used sequentially, with all of the disks not in use effectively being switched off, saving power and greatly reducing temperature, vibration and wear – the three primary disk killers.

The system uses a unique mirrored overlapping-pair writing pattern to provide full data redundancy during the critical writing process. This delivers the redundancy of RAID1 on write, but unlike RAID1, does not require double the number of disks.

Within the array, the use of sequential overlapping mirrored writing pairs requires only two active disks at any one time with the others switched off. This greatly reduces wear and further reduces array vibration and operating temperature. Thus every disk is off, on average, for 95% of the time in the


48-Bay system. Disks automatically switch on for playback, but typically playback from non-writing disks is infrequent and hardly affects the average duty cycle. Hard disk lifetimes of 10 years are achievable.

## Purpose-Designed System

COLDSTORE Opus 4U is built around an industry standard main-board system with a power-efficient CPU and custom disk backplanes.

Even a fully populated 48-Bay, 1248TB array will only use around 175 watts. This low power consumption extends the electronic component lifetime, which, combined with extended disk lifetimes, reduced cooling costs and lower UPS purchase cost, results in a very low overall total cost of ownership for end users.

### COLDSTORE Opus 4U APPLICATION DIAGRAM



The VMS server writes to COLDSTORE Opus across the network. Multiple servers can write to a single COLDSTORE Opus,

or one server can write to multiple COLDSTOREs depending on VMS type. In principle, individual video streams can be

routed to any COLDSTORE on the network under the control of specific types of third-party video management systems.

# ONLY 175W

Low power and high capacity make COLDSTORE Opus 4U an ideal system for long retention of 90 to 180 days or more

Removable drives containing specific time spans enables rapid extraction of critical evidential data for law enforcement purposes.

#### Configuration + Management

COLDSTORE Opus 4U is simple to configure, manage and monitor through Veracity's configuration tool, SITECAPE or via a web browser. These allow automatic device discovery, configuration of settings, analysis of disks and a basic level of diagnostics.

#### Simple Disk Management

COLDSTORE Opus 4U can use almost any make, model and capacity of 3.5" SATA disk drives including any mix of drives. Disks may be added "on the fly" and will automatically be incorporated into the array.

The physical location of specific time spans can be identified through SITECAPE and disks may be extracted for archive or bulk evidential transport if the VMS supports the feature.

Despite being only 4U high, this COLDSTORE Opus can provide up to 1248TB of disk capacity (1222TB effective) at very low power consumption. For example, 1248TB is sufficient for 100 cameras at 6Mbps per camera for over 180 days.

Veracity's configuration tool SITECAPE, combined with the COLDSTORE Opus storage system is user friendly and the hard disks are easy to manage by system integrators and end-users alike.

#### Open Storage System

COLDSTORE Opus is a new system design which supports all brands of Video Management System, allowing customers to use their favoured or existing VMS while taking advantage of all the COLDSTORE benefits for video storage.

#### Other COLDSTORE Models

Veracity provides COLDSTOREs in 2U, 3U and 4U formats with a wide range of disk capacities and capabilities.

The 2U models have 8 bays with up to 208TB and the 3U models can have up to 416TB of disk capacity using 26TB hard disks.

Veracity also offers embedded NVR options for all types of COLDSTORE, combining the NVR recording process with the video storage system in a single unit, scalable to handle large numbers of cameras.

Veracity also offers the LINKLOCK range of very highly cybersecure embedded-recording systems designed for critical national infrastructure applications, including single-camera and mobile devices. See our website for further information.



Back view showing dual hotswap power supplies. This robust unit holds 48 disks.



## TECHNICAL SPECIFICATION

COLDSTORE OPUS®  
4U

## GENERAL

Storage Array Type	Networked attached sequential array running LAID™ writing pattern
Drive Bays	48 x 3.5" (drive bays and screws included)
Interface	Dual ports, 1 x 1 gigabit, 1 x 2.5 gigabit Ethernet ports
Data Throughput	Third-party VMS dependent (unlimited scalability with multiple COLDSTOREs)

## SYSTEM

O.S.	Linux OS on mirrored solid state disks
Time Synchronisation	Via NTP (recommended)
System Integration	Direct from third-party client application
Configuration	Over LAN via Veracity's SITESCAPE application or web browser
Management	Over LAN via Veracity's SITESCAPE application or web browser
Compatibility	Compatible with all third-party VMS systems supporting external storage

## CAPACITY

Disk Capacity	SATA disks of any capacity and almost all makes and models are supported COLDSTORE supports 26TB disks and has forward compatibility for future larger disks. (Check <a href="http://www.veracityglobal.com">www.veracityglobal.com</a> for up-to-date disk capacities)
Array Capacity	Maximum array capacity is currently -1248TB (with current max available 26TB disks) Effective capacity in normal operation - Mirrored Overlapping-Pair - 1222TB

## POWER

Power Supply Type	Dual redundant hot-swappable PSU
Power Supply Rating	110-240V AC Input (Auto sensing)
Power Consumption	175 watts typical maximum (PSU rated at dual 1200W)

## PHYSICAL/ENVIRONMENTAL

Dimensions	19" rack width, 4U high, (W 447mm x H 176mm x D 818mm)
Weight	38.4kg (84.6lbs) including mounting rails but without disks
Operating Temperature	5°C to 50°C (41°F to 122°F)
Relative Humidity	Up to 85%, non-condensing
Compliance	CE, FCC, UKCA, RoHS, NDAA, TAA

## PRODUCT CODES

CSTORE48-4U-OP-UK	COLDSTORE Opus 4U, storage array with mounting rails and UK power cables
CSTORE48-4U-OP-EU	COLDSTORE Opus 4U, storage array with mounting rails and EU power cables
CSTORE48-4U-OP-US	COLDSTORE Opus 4U, storage array with mounting rails and US power cables
VTN-TN-PRO	TIMENET Pro master NTP time server, 5 metre [16.4 feet] cable with antenna

Disk Size	TB	4	6	8	10	12	14	16	18	20	22	24	26
Raw Capacity	TB	192	288	384	480	576	672	768	864	960	1056	1152	1248
Effective Capacity	TB	188	282	376	470	564	646	752	846	940	1030	1128	1222

© Veracity UK Ltd 2026. All rights reserved. DV1.1EN  
Under no circumstances should this document be reproduced,  
distributed or changed, partially or wholly, without written,  
formal authorisation from Veracity UK Ltd.

COLDSTORE, COLDSTORE Opus, SITESCAPE are  
trademarks of Veracity UK Ltd.



Veracity HQ  
Prestwick International Aerospace Park  
4 Dow Road  
Prestwick  
KA9 2TU  
UK  
Tel +44 (0) 1292 264967  
[www.veracityglobal.com](http://www.veracityglobal.com)  
[sales@veracityglobal.com](mailto:sales@veracityglobal.com)

See [www.veracityglobal.com](http://www.veracityglobal.com) website  
for country and region specific contacts.