

TECHNICAL SPECIFICATION

12V DC UNIVERSAL
POWER SUPPLY**POWER INPUT**

Normal Input Voltage	100 - 240V AC
Input Frequency (rated)	50/60Hz
Current (rated)	0.5A at full load

POWER OUTPUT

Normal Output Voltage	12V DC
Maximum Output Current	1.0A
Protection	Over-current, over-voltage and short-circuit protection
Efficiency	> 80%, Level VI

PHYSICAL/ENVIRONMENTAL

Product Case Dimensions	L 49mm W 49mm H 69mm
Weight	130g, 4.59oz
Operating Temperature	0° ~ +40°C, [32°F~ +104°F], Full Load and natural convection
Storage Temperature	-10° ~ +70°C, [14°F~ +158°F]
Operating/Storage Humidity	10 ~ 90% RH (non-cond) / 5 ~ 90% RH (non-cond)
Compliance	EN60950, EN55022B, CE, ROHS, FCC, UL, UKCA, PSE
Format	Plug-top power supply with UK, EU and US plug-in connectors
Output Cable	1.0m, stripped and tinned

ASSOCIATED PRODUCTS

VHW-HW	HIGHWIRE (Ethernet Over Coax adaptor)
VLS-1N-LC	HIGHWIRE Longstar Lite (long distance Ethernet Over Coax adaptor) switch
VLS-1N-L	LONGSPAN Lite (long range network adaptor)
VLT-SC100	LIGHTSPAN SC100 (Ethernet to fibre media converter)
VLT-SC100-BB	LIGHTSPAN SC100 Backbox (Ethernet to fibre media converter)
VTN-TN-PRO	TIMENET Pro (GPS-based master NTP time server)

PRODUCT CODES

VPSU-12V-U	12V DC Universal plug-top power supply
------------	--



veracity

Veracity HQ
Prestwick International Aerospace Park
4 Dow Road
Prestwick
UK
KA9 2TU
Tel +44 (0) 1292 264967

www.veracityglobal.com
sales@veracityglobal.com

See www.veracityglobal.com website
for country and region specific contacts.

© Veracity UK Ltd 2023. All rights reserved. DV1.0EN

*Under no circumstances should this document be reproduced,
distributed or changed, partially or wholly, without written,
formal authorisation from Veracity UK Ltd.*

HIGHWIRE, HIGHWIRE Longstar®, LONGSPAN®,
LIGHTSPAN®, are trademarks of Veracity UK Ltd.