

POWER OVER ETHERNET SPLITTER
OUTBREAK™

POE splitter for delivering power via POE to non-POE network devices

Delivers 5V or 12V DC to non-POE devices from a POE network source by splitting data and power.

- | Simple POE splitter delivering clean power to non-POE devices
- | Fully IEEE 802.3af compliant and gigabit compatible
- | Steps down POE voltage (48V) to 5V or 12V DC
- | Compact unit with integral wall mount lugs
- | Ideal for non-POE wireless access points, IP phones, IP cameras

TECHNICAL SPECIFICATION

OUTBREAK™

| | | | |
|-------------------------------|--|--------------|------------------|
| POWER | | | |
| Input voltage | 36V to 56V DC, receiving power on either data or spare pairs | | |
| Input current | 0.6A at 36V maximum load | | |
| OUTPUT POWER | | | |
| OUTBREAK 5 | 12.5 watts at 5V DC | | |
| OUTBREAK 12 | 12-14 watts at 12V DC | | |
| | Output with short-circuit protection | | |
| DC Output connector | Barrel connector 9mm x 2.5mm x 5.5mm, centre positive | | |
| POE STANDARDS | | | |
| | IEEE 802.3af POE | | |
| ETHERNET INTERFACE | | | |
| | RJ45 Data and POE IN port | | |
| | RJ45 Data OUT port | | |
| | 10/100/1000 Base-T compatible | | |
| LEDS | | | |
| Status indicator | Green LED ON - Output OK | | |
| PHYSICAL/ENVIRONMENTAL | | | |
| Dimensions | L 100mm (excluding flying lead) W 56mm H 28mm | | |
| Weight | 200g [7.0oz] | | |
| Mounting | Integral wall-mount lugs | | |
| Operating temperature | 0°C to +40°C [32°F to 104°F] | | |
| Relative humidity | 5% to 90% non-condensing | | |
| Compliance | CE, FCC, RoHS, UKCA | | |
| PRODUCT CODES | | | |
| | VOR-OB5 | OUTBREAK 5V | 5V POE Splitter |
| | VOR-OB12 | OUTBREAK 12V | 12V POE Splitter |



OUTBREAK 12V

OUTBREAK 5V



Veracity HQ
 Prestwick International Aerospace Park
 4 Dow Road
 Prestwick
 UK
 KA9 2TU
 Tel +44 (0) 1292 264967

www.veracityglobal.com
sales@veracityglobal.com

See www.veracityglobal.com website
 for country and region specific contacts.